


Sentinel-3 SLSTR Marine User Handbook

This Document is Public



Doc.No. : EUM/OPS-SEN3/MAN/17/921927
Issue : v1B e-signed
Date : 21 November 2017
WBS/DBS :

EUMETSAT
Eumetsat-Allee 1, D-64295 Darmstadt, Germany
Tel: +49 6151 807-7
Fax: +49 6151 807 555
<http://www.eumetsat.int>

This Document is Public

Document Change Record

<i>Issue / Revision</i>	<i>Date</i>	<i>DCN. No</i>	<i>Changed Pages / Paragraphs</i>
V1B	21 November 2017		First issue

*This Document is Public***Table of Contents**

1	INTRODUCTION.....	6
1.1	Purpose and Scope.....	6
1.2	Applicable Documents	6
1.3	Reference Documents	6
1.4	Document Structure	6
1.5	List of acronyms and abbreviations	7
2	BACKGROUND	9
2.1	Overview	9
2.2	Disclaimer.....	9
2.3	Useful links	9
2.4	Limitations of the SLSTR SST Products	9
2.5	History of product changes	9
3	COPERNICUS AND SLSTR.....	10
3.1	Overview of Copernicus	10
3.2	Overview of Sentinel-3	10
3.3	Complementarities with other SST missions	10
3.4	SLSTR.....	12
3.5	Measurement of SST from SLSTR	13
3.6	SLSTR products	13
3.6.1	Expected accuracy.....	14
3.7	Quality control and monitoring	14
3.8	Where to go for further information (ATBDs)	15
4	SLSTR DATA PROCESSING.....	16
4.1	Level-1 Processing Approach	16
4.2	Level-2 Processing Approach	17
5	SLSTR PRODUCTS.....	19
5.1	File naming.....	19
5.2	Data format.....	20
5.3	Level 1 Product Contents	20
5.4	Level 2 Product Contents	21
6	HELPDESK, PRODUCT DISSEMINATION AND ARCHIVE	23
6.1	Helpdesk	23
6.2	Data access routes	23
6.3	User Products Dissemination Concept.....	24
6.4	Software Tools	25
6.4.1	Sentinel-3 Toolbox	25
6.4.1.1	Installing the toolbox.....	25
6.4.1.2	Opening a Sentinel-3 product.....	25
6.4.1.3	Basic functionality.....	26
6.4.2	View the contents of a NetCDF file?	27
6.4.3	Cerbera and Felyx	27
7	DATA QUALITY	28
8	USER BEWARE!	29
8.1.1	Product Grids in RBT and WCT Products	29
8.1.2	Aligning the product grids in RBT and WCT Products.....	29
8.1.3	Mixed SST fields in WST Product.....	30
8.1.4	Quality level and SSES in WST Product	30
8.1.5	Data over all water bodies in WCT and WST Products	30
8.1.6	NeDT in WST product.....	31

This Document is Public

8.1.7	Using flags in RBT and WCT Product.....	31
8.1.8	Converting from Brightness Temperature to Radiance in RBT Product.....	33
8.1.9	Converting from Radiance to Reflectance in RBT Product	33
8.1.10	Range of valid brightness temperatures in channels S7, S8 and S9	33

Table of Figures

Figure 1: SLSTR Level 1 RBT instrument grid processing	16
Figure 2: SLSTR Level 1 RBT image grid processing	17
Figure 3: SLSTR file format.....	20
Figure 4: Data access routes	23
Figure 5: (Left) Example SLSTR product grids showing the tie-point (blue), nadir (green and oblique (red) geodetic coordinates. The SSP is indicated by the black line.	29
Figure 6: (Left) Full swath WST SST image and (right) “sst_algorithm_type” showing the dual-view (cyan) and nadir-only (purple) regions.	30
Figure 7: SLSTR SST image of the Amazon estuary in South America showing the scale of inland water bodies provided in SLSTR data.....	30
Figure 8: Example NeDT image for channel S8	31

Table of Tables

Table 1: SLSTR Spectral Bands	12
Table 2: Data access locations	24
Table 3: SLSTR validation against drifters.....	28
Table 4: SLSTR confidence bitmask.....	32
Table 5: SLSTR cloud bitmask	32

1 INTRODUCTION

1.1 Purpose and Scope

The Sentinel-3 Sea and Land Surface Temperature Radiometer (SLSTR) Marine Handbook is a guide that summarises the key information needed for an end-user (both general and specialist) to gain a better understanding of the SLSTR marine Level 1 (L1) and Level 2 (L2) products. Where the information is not held in the handbook itself, the user is pointed to further (primarily internet-based) resources.

1.2 Applicable Documents

AD-1	Sentinel-3 Mission Requirements Document, v2.0	EOP-SMO/1151/MD-md
AD-2	Sentinel-3 Mission Requirements Traceability Document, v1.0	EOP-SM/2184/CD-cd
AD-3	Sentinel-3 PDGS File Naming Convention, v1D	EUM/LEO-SEN3/SPE/10/0070

1.3 Reference Documents

RD-1	Allison, L.J., and J. Kennedy, 1967. An Evaluation of Sea Surface Temperature as Measured by the Nimbus I High Resolution Infrared Radiometer,” NASA Technical Note No. D-4078, National Aeronautics and Space Administration, Washington, D.C.
RD-2	Donlon C., N. Rayner, I. Robinson, D. J. S. Poulter, K. S. Casey, J. Vazquez-Cuervo, E. Armstrong, A., Bingham, O. Arino, C. Gentemann, D. May, P. LeBorgne, J. Piollé, I. Barton, H. Beggs, C. J., Merchant, S. Heinz, A. Harris, G. Wick, B. Emery, P. Minnett, R. Evans, D. Llewellyn-Jones, C., Mutlow, R. W. Reynolds, H. Kawamura, 2007. The Global Ocean Data Assimilation Experiment High-resolution Sea Surface Temperature Pilot Project, Bulletin of the American Meteorological Society, Volume 88, Issue 8 (August 2007) pp. 1197-1213 doi: http://dx.doi.org/10.1175/BAMS-76788-8-1197 .
RD-3	P. Le Borgne, A. Marsouin, F. Orain, H. Roquet, 2012. Operational sea surface temperature bias adjustment using AATSR data, Remote Sensing of Environment, 116, 93-106. doi:10.1016/j.rse.2010.02.023.
RD-4	Závody, A.M., Mutlow, C.T., and Llewellyn-Jones, D.T., 1995. A Radiative Transfer Model for Sea Surface Temperature Retrieval from the Along-Track Scanning Radiometer. Journal of Geophysical research, 100, 937-952.
RD-5	Merchant, C.J., Harris, A.R., Murray, M.J., and Závody, A.M., 1999. Toward the Elimination of Bias in Satellite Retrieval of Sea Surface Temperature 1. Theory, Modelling and Interalgorithm Comparison. Journal of Geophysical Research, 104, 23565-23578.
RD-6	Bulgin, C.E., O. Embury, G. Corlett, C.J. Merchant, 2015. Independent uncertainty estimates for coefficient based sea surface temperature retrieval from the Along-Track Scanning Radiometer, Remote Sensing of Environment, 162, 396-407

1.4 Document Structure

Section 1 General information (this section).

Section 2 Some background information on SLSTR and its marine products.

This Document is Public

- Section 3 Provides an overview of Copernicus and the SLSTR instrument.
- Section 4 Gives a description of SLSTR L1 and L2 marine processing.
- Section 5 Gives a description of SLSTR L1 and L2 marine products.
- Section 6 Explains how to download and visualise SLSTR data.
- Section 7 Summarises the data quality of SLSTR marine products.
- Section 8 Provides details of some unique features of SLSTR and SLTR marine products that any user should be aware of.

1.5 List of acronyms and abbreviations

AATSR	Advanced Along-Track Scanning Radiometer
ATBD	Algorithm Theoretical Basis Document
Cal/Val	Calibration and Validation
CMEMS	Copernicus Marine Environment Monitoring Service
CODA	Copernicus Online Data Access
ECMWF	European Centre for Medium-Range Weather Forecasts
EO	Earth Observation
EOP	Earth Observation Portal
EUMETSAT	European Organisation for the Exploitation of Meteorological Satellites
FTP	File Transfer Protocol
GHRSSST	Group for High Resolution SST
GMES	Global Monitoring for Environment and Security
IR	Infrared
L1	Level 1
L2	Level 2
LST	Land Surface Temperature
MDB	Match-up Database
METIS	Monitoring and Evaluation of Thematic Information from Space
MRD	Mission Requirements Document
MRTD	Mission Requirements Traceability Document
MWR	Microwave Radiometer
NDVI	Normalised Difference Vegetation Index
NeDT	Noise Equivalent Differential Temperature
NetCDF	Network Common Data Format
NRT	Near Real-Time
NTC	Non-Time Critical
OSI SAF	Ocean and Sea Ice Satellite Application Facility
PDGS	Payload Data Ground Segment
PDU	Product Dissemination Unit
POD	Precise Orbit Determination
RBT	Radiance Brightness Temperature
S3VT	Sentinel-3 Validation Team
SAFE	Standard Archive Format for Europe

This Document is Public

SLSTR	Sea and Land Surface Temperature Radiometer
SNAP	SeNtinel Application Platform
SRAL	S Altimeter
SST	Sea Surface Temperature
STEP	Science Toolbox Exploitation Platform
SWIR	Short-wave Infrared
TIR	Thermal Infrared
TOA	Top of Atmosphere
VNIR	Visible Near Infrared
VISCAL	Visible Calibration
WCT	Internal individual algorithms Sea Surface Temperature
WST	GHR SST L2P format Sea Surface Temperature

2 BACKGROUND

2.1 Overview

The Sea and Land Surface Temperature Radiometer (SLSTR) is a dual-view multi-spectral radiometer on-board the Sentinel-3 series of spacecraft that are part of the European Union's Copernicus programme.

2.2 Disclaimer

The use of these products is granted to every interested user free of charge.

EUMETSAT is very much interested in receiving your feedback. Your feedback helps us in improving product quality and maintaining the resources for the EUMETSAT marine services.

2.3 Useful links

EUMETSAT Copernicus homepage:

www.eumetsat.int/website/home/Satellites/FutureSatellites/CopernicusSatellites/CopernicusResources/

EUMETSAT Sea Surface Temperature homepage:

<http://www.eumetsat.int/website/home/Data/CopernicusServices/Sentinel3Services/SeaSurfaceTemperature/index.html>

EUMETSAT YouTube home:

<https://www.youtube.com/channel/UCiN59j5b1fAGnXVzIYFpaMw>

Copernicus YouTube playlist

<https://www.youtube.com/playlist?list=PLOQg9n6ApiflODObv39j43j8IAvJDOAVY>

How to access Copernicus sea surface temperature data

<https://youtu.be/lKyUeN3uS0Q>

Sentinel-3 for oceans:

https://www.youtube.com/watch?v=T9WCWnk_qN4

Sentinel-3 playlist:

<https://www.youtube.com/playlist?list=PLbyvawxScNbus9n8rmw0GElhPqrCwcsiD>

2.4 Limitations of the SLSTR SST Products

See product notices for known limitations of SLSTR products (available from EUMETSAT at):

<https://www.eumetsat.int/website/home/Data/CopernicusServices/Sentinel3Services/SeaSurfaceTemperature/index.html>).

2.5 History of product changes

See product notices for the history of product changes (available from EUMETSAT at):

<https://www.eumetsat.int/website/home/Data/CopernicusServices/Sentinel3Services/SeaSurfaceTemperature/index.html>).

This Document is Public

3 COPERNICUS AND SLSTR

EUMETSAT provides Earth Observation (EO) data, products and support services to the Copernicus information services and user communities, with a focus on marine, atmosphere and climate.

3.1 Overview of Copernicus

Copernicus is a European Commission Programme for the establishment of a European capacity for EO and monitoring. It encompasses space, *in situ* and service components, with the space component including the Sentinel missions. Of these, Sentinel-3A was launched in February 2016 with Sentinel-3B due to launch in late 2017 to provide at least two satellites in orbit at any one time.

3.2 Overview of Sentinel-3

The Sentinel-3 satellites are Earth polar-orbiting satellites, operating at an average altitude of 815 km above the surface with a repeat cycle of roughly 27 days. They each carry a set of three instruments focusing on high-accuracy optical, radar and altimetry data for marine and land services:

- Ocean and Land Colour Instrument (OLCI) for medium resolution marine and terrestrial optical measurements;
- Sea and Land Surface Temperature Radiometer (SLSTR) for marine and terrestrial thermal measurements;
- SAR Radar Altimeter (SRAL) together with the Microwave Radiometer (MWR) and Precise Orbit Determination (POD) for topography measurements.

The specific objectives for the Sentinel-3 missions are defined in the Mission Requirements Document (MRD) [AD-1], which is adopted in a traceable format through the Mission Requirements Traceability Document (MRTD) [AD-2].

The Copernicus Marine Environment Monitoring Service (CMEMS) provides regular and systematic core reference information on the state of the physical oceans and regional seas to support marine applications. The products come from both EO data and numerical modelling.

3.3 Complementarities with other SST missions

The retrieval of sea surface temperature (SST) from satellite-based infrared (IR) radiometers was first reported in 1967 [RD-1]. Since then many instruments have flown and the provision of sea SST data for operational oceanography by the Group for High Resolution SST, GHRSST [RD-2], has grown to a mature sustainable and essential service. The GHRSST partners offer a suite of tailored global high-resolution SST products, in near-real-time, daily, to support operational forecast systems and the broader scientific community.

SST is the kinetic temperature of a water body at a defined depth. Although SLSTR measures a radiometric temperature it is provided as a kinetic temperature by considering the emissivity of the water body as part of the SST retrieval process. Due to the limited penetration of thermal

This Document is Public

infrared (IR) radiation through the water column, the IR radiometric temperature measured by SLSTR is that of only the top few tens of micrometres referred to as the skin temperature. At night, the skin temperature is typically a few tenths of a degree cooler than the temperature measured by in situ systems; in the day, the skin can be considerably higher if strong diurnal warming is present. For more details please see “What is SST?” on the GHRSSST web pages (<https://www.ghrsst.org/ghrsst-data-services/products/>).

GHRSSST relies on SST data from both space and *in situ* measurement systems. From space, SST can be estimated from radiometric wavelengths in the so-called atmospheric window regions, regions in the black-body emission of the Earth that are least sensitive to the atmosphere. These occur in the IR and microwave regions although the lower signal strength from the Earth’s Planck radiation curve in the microwave region results in lower accuracy than that achievable in the IR.

In addition to multiple wavelengths it is possible to obtain SST from satellites operating in different orbits. Currently, IR sensors operate in both low and geostationary Earth orbits; microwave are limited to low Earth orbit for now owing to the low signal. This means GHRSSST relies on data from three types of satellite radiometer:

- Polar orbit IR
- Polar orbit microwave
- Geostationary orbit IR

All the data available to GHRSSST requires some means of reference field to provide the best possible estimate from the ensemble. This is usually *in situ* data but previous work with AATSR demonstrated that a satellite radiometer could be used if it was sufficiently accurate [RD-3]. This is where SLSTR comes in – as the successor to AATSR in providing reference quality SSTs from space. For this, SLSTR has three unique features:

- A dual-view for improved atmospheric correction
- Highly stable cooled detectors
- Two on-board black bodies for calibration of each scan

In addition to providing reference quality SSTs in the dual-view part of the swath (700 km), SLSTR also provides nadir-only SSTs over the remaining swath (up to 1400 km).

This Document is Public

3.4 SLSTR

SLSTR is a dual-view multichannel satellite radiometer. It has nine spectral bands that detect top of atmosphere (TOA) radiation in the VNIR/SWIR/TIR regions, which are summarised in Table 1 below.

Band	λ centre (μm)	Width (μm)	Function	Comments		Res. (m)
S1	0.555	0.02	Cloud screening, vegetation monitoring, aerosol	Visible Near IR (VNIR)	Solar reflectance bands	500
S2	0.659	0.02	NDVI, vegetation monitoring, aerosol			
S3	0.865	0.02	NDVI, cloud flagging, Pixel co-registration			
S4	1.375	0.015	Cirrus detection over land	Short-Wave IR (SWIR)		
S5	1.61	0.06	Cloud clearing, ice, snow, vegetation monitoring			
S6	2.25	0.05	Vegetation state and cloud clearing			
S7	3.74	0.38	SST, LST, Active fire	Thermal IR bands (TIR)		1000
S8	10.85	0.9	SST, LST, Active fire			
S9	12	1	SST, LST			
F1	3.74	0.38	Active fire	Thermal IR fire bands (TIRf)		
F2	10.85	0.9	Active fire			

Table 1: SLSTR Spectral Bands

Although primarily designed for sensing the temperature of the Earth’s surface, the additional bands at shorter wavelengths are required to aid with removing cloud and aerosol from the temperature estimate; in turn, by characterising the surface, these additional channels can then be exploited to provide estimates of cloud and aerosol geophysics as well.

The SLSTR instrument exploits two independent scan chains to provide a wider instrument swath than its predecessor ATSR’s but maintaining a common angle of incidence. The two swaths have slightly different coverage:

- Nadir view swath is ~ 1400 km across track
- Oblique view swath is ~ 740 km across track

This Document is Public

The SLSTR nadir swath is asymmetrical with respect to its sub-satellite point (SSP) to provide identical and contemporaneous coverage with OLCI ocean/land colour measurements. The SSP is in the centre of the grid in the oblique view. To find the SSP you can either (1) use the field *track_offset* in the product or manifest file, or (2) find the point at which the *Cartesian* x-coordinate is minimal.

SLSTR products are generated separately in the two instrument views, and at two spatial resolutions, depending on optical channels:

- 500 m resolution for solar reflectance bands S1 to S6
- 1 km resolution for thermal infrared bands S7 to S9 and F1 & F2

Owing to its conical scan geometry, the SLSTR products are provided on a nominal raster image grid through nearest neighbour resampling and not in their original orientation. However, the products do contain the required information to reconstruct the original scan locations if a user deems it necessary for their application.

3.5 Measurement of SST from SLSTR

The SLSTR series of instruments have three spectral bands that are used for SST retrieval, with nominal band centres at 3.7 μm , 11 μm and 12 μm . During the day, the 3.7 μm channel is not used due to solar contamination and so, as each Earth scene is viewed in both nadir and off-nadir, there are four possible retrieved SSTs, referred to as N2 (nadir-only 11 μm and 12 μm), N3 (nadir-only 3.7 μm , 11 μm and 12 μm), D2 (dual-view 11 μm and 12 μm) and D3 (dual-view 3.7 μm , 11 μm and 12 μm). The N2, N3, D2 and D3 nomenclature is used through the rest of this report. Note: The L2P product only contains the best SST available and does not therefore contain nadir-view only SSTs.

The retrieval scheme itself uses linear regression algorithms with coefficients derived from radiative transfer models (see for example [RD-4, RD-5]) that perform a linear regression of SST to simulated brightness temperatures (BTs) at the nominal band centres. Multiple channels are used for atmospheric correction (mainly water vapour) with the use of multiple views accounting for aerosol effects.

3.6 SLSTR products

SLSTR Level-1 RBT and Level-2 WST data products are freely available to the public. The SLSTR files are collected into a SAFE container containing free-standing NetCDF-4 format files. The timeframe for delivery of products is dependent on specific applications:

- **Near Real-Time** (NRT) products, are available in less than 3 hours after acquisition of data by the sensor.

This Document is Public

- **Non-Time Critical** (NTC) products, are available not later than 1 month after acquisition or from long-term archives. Typically, the product should be available within 24h or 48h (but this not guaranteed).

3.6.1 Expected accuracy

The expected accuracy is defined as the expected bias and standard deviation of the primary calculations. The accuracy is validated against in situ measurements from buoys, platforms, or ship, and against NWP data.

All products contain uncertainty estimates in two type:

1. GHRSSST SSES

These are standard GHRSSST Single Sensor Error Statistics (SSES) bias and standard deviation estimates from comparison to in situ data

2. Theoretical uncertainties

These are experimental estimates of the SST uncertainty calculated per pixel from the output of the radiative transfer modelling. The scheme is based on [RD-6].

The Sentinel-3 Mission Requirements Document [AD-1] states that:

- Sentinel-3 shall provide SST measurement capability to at least the quality of AATSR on Envisat: SST shall be accurate to $< 0.3 \text{ K}$ @ 1 km spatial resolution and with improved swath coverage). [S3-MR-400].
- Sentinel-3 SST measurements shall have a long-term radiometric stability goal of 0.1 K/decade ($\leq 0.2 \text{ K/decade}$ threshold) for a 5×5 latitude longitude area. [S3-MR-980].

A summary of current data quality and estimated accuracy is given in Section 7.

3.7 Quality control and monitoring

Quality control and monitoring of SLSTR is carried out by several entities. The Mission Performance Centre (MPC) is responsible for calibration, validation, quality control and end-to-end system performance assessment. The MPC includes the SLSTR Expert Support Laboratory (ESL) for specific calibration/validation, off-line quality control and algorithm correction and evolution activities. The primary method for reporting of data quality is the SLSTR Cyclic Report. These are generated every cycle (roughly every 27 days or 501 orbits) and can be downloaded from:

<https://sentinel.esa.int/web/sentinel/technical-guides/sentinel-3-slstr/data-quality-reports>.

EUMETSAT also supports additional quality control and monitoring for the SLSTR marine products. This comes in two forms:

- **The SLSTR Match-up Database (MDB)**

The SLSTR MDB contains temporal and spatial coincidences between SLSTR and various reference dataset, e.g. drifting buoys. It is generated by the EUMETSAT Ocean and Sea Ice Satellite Application Facility (OSI-SAF).

This Document is Public

- **Monitoring & Evaluation of Thematic Information from Space (METIS)**

The Monitoring and Evaluation of Thematic Information from Space (METIS) tool is developed to monitor EUMETSAT operational remotely sensed products for stability, quality and performance on a global and regional basis in routine. The METIS-SST module provides near-real time diagnostics of all EUMETSAT operational L2 satellite SSTs: Sentinel-3A SLSTR, METOP-B AVHRR and METOP-B IASI.

You can access METIS at <http://metis.eumetsat.int/>.

3.8 Where to go for further information (ATBDs)

The details of all SLSTR algorithms are provided in within an Algorithm Theoretical Basis Document (ATBD). For SLSTR Marine products the relevant documents are publically accessible from EUMETSAT's Copernicus Sea Surface Temperature webpage¹.

SLSTR Level 2 SST ATBD	SLSTR-ATBD-L2SST-v2.5 Version 2.5
SLSTR Level 1 ATBD	S3-TN-RAL-SL-032 Version 2
Sentinel-3 Product Data Format Specification	S3IPF.PDS.005 Version 2.3

In addition, interested readers may wish to consult the ESA user and technical guides for additional details:

ESA SLSTR User guide	https://earth.esa.int/web/sentinel/user-guides/sentinel-3-slstr
ESA SLSTR Technical guide	https://earth.esa.int/web/sentinel/technical-guides/sentinel-3-slstr

¹ EUMETSAT's sea surface temperature webpage:
<http://www.eumetsat.int/website/home/Data/CopernicusServices/Sentinel3Services/SeaSurfaceTemperature/index.html>

This Document is Public

4 SLSTR DATA PROCESSING

The SLSTR operational processor is divided in to three major processing levels:

- **Level 0**
This step processes raw data contained in instrument source packets. Level 0 products are internal products, and are not disseminated to users.
- **Level 1**
This step processes the Level 0 data to geo-located radiometric measurements for each SLSTR channel/view.
- **Level 2**
This step processes the Level 1 data to geophysical data (e.g. sea surface temperature, land surface temperature).

4.1 Level-1 Processing Approach

SLSTR Level 1 processing is divided into two main steps:

- Instrument grid-processing
- Image grid-processing

The instrument grid-processing has five sub-steps:




Figure 1: SLSTR Level 1 RBT instrument grid processing

First the source packets from the instrument are processed. Next the data is calibrated: For the IR channels this involves calculating the calibration offset and slope that describes the linear relationship between numerical counts and radiance; for the VIS/NIR/SWIR channels, the calibration is based on a diffuse calibration (VISCAL) target of accurately known reflectance

This Document is Public

which is illuminated by the sun over a short segment of the orbit to enable a linear calibration relationship between the measured signal in each channel and the surface reflectance to be determined. Finally, the time and geolocation are calculated for each pixel.

The image grid-processing re-grids the SLSTR measurements onto the nominal raster image, and tests each pixel for cloud. It also contains five sub-steps:




Figure 2: SLSTR Level 1 RBT image grid processing

In the re-gridding, the across and along track indices are calculated for each instrument pixel on either a 1 km raster image grid for the thermal IR channels or a 0.5 km grid for the visible, NIR and SWIR channels. The re-gridding is done by nearest neighbour resampling. Missing image pixels are then cosmetically filled.

The data is strictly speaking not cosmetic, i.e. it is not made up, it is simply that an instrument pixel might be used more than once. Instrument pixels that are not used in generating the image pixels are included in the orphan pixels' containers.

Surface Classification and the Basic Cloud Masking are then applied to each image pixel. Finally, the ECMWF meteorological fields are added on a sub-grid referred to as the tie-point grid.

4.2 Level-2 Processing Approach

SLSTR Level-2 marine processing includes two primary steps:

- SST processing to generate five single-algorithm SST products using the method described in Section 3.5. These are provided in the Level 2 WCT product. The SSTs included are:
 - **1 km N2 SST**
 - Nadir single view using channels S8 and S9, i.e. 10.85 and 12 μm

This Document is Public

- **1 km N3 SST**
 - Nadir single view and all thermal channels (N2 plus S7, i.e. 3.7 μm)
- **1 km N3R SST**
 - Like N3 but using the property of "aerosol robustness" and its associated method described in [RD-5]
- **1 km D2 SST**
 - Like N2, except that BTs in both the oblique and nadir views are used
- **1 km D3 SST**
 - Like N3, except that both views are used.
- The L2P processing module, which generates a Group for High Resolution Sea Surface Temperature (GHR SST) compliant product. The L2P product contains only the best available SST for each pixel according to a set of rules define in the SLSTR Level 2 SST ATBD. In an extra step compared to the WCT product, the WST SSTs are atmospherically smoothed to reduce noise introduced in the retrieval process. Further details of the smoothing can be found in the SLSTR Level 2 SST ATBD. The L2P format data file is provided in the Level 2 WST product.

5 SLSTR PRODUCTS

There are three SLSTR marine product types that are disseminated to users:

- **Level 1 RBT**

This product provides radiances and brightness temperatures for each pixel, view and channel.

- **Level 2 WCT** (only available to Cal/Val users via S3VT)

This product provides sea surface temperature for all offered retrieval algorithms.

- **Level 2 WST**

This product provides the best SST at each SLSTR location in GHRSSST L2P format.

SLSTR products are uniquely defined by their processing baseline configuration. This indicates both the software version used to generate the product as well as the specific set of auxiliary files used. This information is not currently available within the SLSTR products but can be found in the product notices.

5.1 File naming

The file naming is based on a sequence of fields [AD-3]:

```
MMM_SS_L_TTTTTT_YYYYMMDDTHHMMSS_YYYYMMDDTHHMMSS_YYYYMMDDTHHMMSS_
<instance ID>_GGG<class ID>.<extension>
```

Which for Sentinel-3 SLSTR data would be, for example:

```
S3A_SL_1_RBT_20160509T103945_20160509T104245_20160509T124907_
0180_004_051_1979_SVL_O_NR_001.SEN3
```

- **MMM** – Mission id, e.g. S3A
- **SS** - Data source/consumer, e.g. SL is for SLSTR
- **L** - Processing level, e.g. 1 for L1 and 2 for L2
- **TTTTT** - Data Type ID, e.g.
- “RBT___” = TOA radiances and brightness temperatures
- “WCT___” = Retrieved SST for all algorithms
- “WST___” = Best SST in GHRSSST L2P format
- **YYYYMMDDTHHMMSS** - 15 character **Data Start** time, then **Data Stop** time then **Creation Date**
- **<instance id>** - 17 characters e.g. 0180_004_051_1979 is duration, cycle number, relative orbit number and frame along track coordinate
- **GGG** – Product Generating Centre e.g., EUM = EUMETSAT and SVL = Svalbard Satellite Core Ground Station
- **<class ID>** - 8 characters to indicate the processing system e.g., O_NR_001 is the software platform (O for operational, F for reference, D for development and R for reprocessing), processing workflow (NR for NRT, ST for STC and NT for NTC) and 3 letters/digits indicating the baseline collection.
- **<extension>** - Filename extension, SEN3

This Document is Public

5.2 Data format

The SLSTR data format follows the format defined for each Sentinel-3 product, i.e. the PDGS product specification, and is based on Sentinel-SAFE. Each product package includes:

- A manifest file containing a metadata section and a data object section (in XML format).
- At least one measurement or annotation data files (in NetCDF-4 format).

The manifest file - xfdumanifest.xml - explains the contents of the package at an overarching level.




Figure 3: SLSTR file format

5.3 Level 1 Product Contents

The SLSTR Level 1 RBT product is composed of one manifest file and several measurement and annotation data files (between 77 and 111 files depending on the processing parameters). For thermal IR and fire channels (labelled as S7 to S9 and F1, F2 for fire channels), the radiometric measurements are expressed in TOA Brightness Temperature (BT). In the case of visible / NIR / SWIR channels (labelled as S1 to S6 channels), these measurements are expressed in TOA radiances.

The radiometric measurements are indexed according to the across track and along track direction:

- On a 1 km grid for brightness temperature
- On a 0.5 km grid for radiances. In this case, three stripes are distinguished: A, B and TDI, with TDI a derived product from A and B stripes. Only the stripes selected in the processing configuration file are available.

They contain, for each pixel on the full resolution grid and for each orphan pixel, the radiance or brightness temperature and their associated exception flags. These files are all written in NetCDF-4 format and include dimensions, variables and associated attributes.

The SLSTR Level 1 RBT product also contains annotation data files are also written in NetCDF-4 format:

- Quality flags concerning cloud flagging and scan and flip mirror positions
- Surface pixel classification information

This Document is Public

- Meteorological annotations
- Quality annotations, such as estimates of detector noise measured at VISCAL or black bodies
- Arrays of indices to retrieve the position of each pixel in the instrument measurement frame
- Cartesian and geodetic coordinates associated with the radiometric measurements and the tie-point grid defined for SLSTR.

5.4 Level 2 Product Contents

The SLSTR Level 2 products are composed of one manifest file and between 1 and 21 files depending on the package several measurement and annotation data files depending on the product.

The measurement and annotation data files are in NetCDF-4 format, and include dimensions, variables and associated attributes. The included parameters are provided only on the 1 km grid, indexed by their along and across track indices. For measurement files:

- **SL 2 WCT:**
Contains five sea surface measurement files. These five SST measurement datasets are generated on the 1 km image grid and are indexed across track and along track. In addition to SST, the Level 2 WCT provides the SST uncertainties and exception flags derived from SLSTR Level 1 RBT product, and includes parameters directly taken from SLSTR Level 1 RBT product, associated with re-gridded and orphan pixels:
 - Quality flags concerning cloud flagging and scan and flip mirror testing
 - Arrays of indices to retrieve the position of each pixel in the instrument measurement frame and their time stamps
 - Cartesian and geodetic coordinates associated to the radiometric measurements and to the tie-points grid defined for SLSTR
 - Meteorological annotations.
- **SL 2 WST:** One measurement file, giving the latitude, longitude, time and sea surface temperature value, in GHRSSST L2P format. It includes a single SST field derived from the best performing single-coefficient SST field for any given part of the swath, plus several auxiliary fields to aid interpretation of the SST field. Each SST, previously generated during in the Level 2 WCT product, is atmospherically smoothed using a 3 by 3 pixel average of the difference between the SSTs and the mean S8 BT value.

The file provides standard GHRSSST required fields, including:

This Document is Public

- Latitude and longitude of each pixel
- The SST value
- The SST measurement time deviation from a reference time
- The Single Sensor Error Statistic (SSES) bias and standard deviation
- A quality flag per pixel
- Additional parameters (wind speed at 10 m, the fractional sea-ice contamination, the aerosol contamination indicator for each pixel) to aid in using the SST value

In addition, several experimental fields are provided giving:

- The algorithm used to generate the SST
- The difference between the dual-view and nadir-only SSTs for the dual-view part of the swath
- TOA BTs and NeDTs
- Pixel level theoretical uncertainties

This Document is Public

6 HELPDASK, PRODUCT DISSEMINATION AND ARCHIVE

6.1 Helpdesk

The EUMETSAT User Helpdesk is available to all users during standard office hours. The service provides support on data access and product usage and application. All user requests on the EUMETSAT SLSTR Marine data products should be directed to the EUMETSAT Help Desk ops@eumetsat.int.

6.2 Data access routes

EUMETSAT provides data access through several routes, depending on your preferred delivery route and the latency of the data that's needed. This central catalogue lists all EUMETSAT missions (Meteosat, Metop, and Jason-2) in addition to the Copernicus Sentinel-3 marine and atmosphere products.




Figure 4: Data access routes

The starting point is usually the EUMETSAT EO Portal (EOP) for which you need to create a user account. Please see the online tutorial for further information -> [Earth Observation Portal Tutorial - Registering](#). Once registered you can then access Copernicus Sentinel-3 marine products from the links in the following table. If you already have an EOP account then please request access to the other services by emailing the EUMETSAT Help Desk.

This Document is Public





	EUMETCast eumetcast.com	Multi service push dissemination system based on multicast technology, which is transported to the user via satellite (EUMETCast Satellite, with coverage over Europe, the Middle-East and Africa).
	CODA coda.eumetsat.int	Download service offers all Sentinel-3 marine and atmospheric products through a rolling buffer that (at a maximum) will span 12 months.
	Data Centre Long-Term Archive archive.eumetsat.int	Ordering application that enables users to browse and select from EUMETSAT's long-term archive products, including the Copernicus Sentinel-3 marine and atmospheric products.
	EUMETView eumetview.eumetsat.int	A visualisation service that allows users to view EUMETSAT's data and Copernicus Sentinel-3 marine data in an interactive way using an online map view.

Table 2: Data access locations

- For those who would like to receive the data over a satellite connection: EUMETCast is EUMETSAT's primary dissemination method.
- For those downloading data from the internet: If you are interested in just recently acquired data then the best access route is the Copernicus Online Data Access (CODA) that provides an interactive interface. Batch scripting is also possible. In order to discover CODA's functionalities and example scripts to download Sentinel-3 data using CODA APIs, read the User Guide: <https://coda.eumetsat.int/manual/CODA-user-manual.pdf>.
- If you would like to access an historical time-series: The Data Centre would be your route; this allows you to access either the global dataset (under the Products tab, best entering OLCI as a search term so you see just these products), or large regions of interest such as the North Atlantic and Mediterranean Sea (under the Sentinel-3 Datasets tab). On subsequent screens, you can then define a region of interest and time-range before ordering the products.

For those who are members of the Sentinel-3 Validation Team (S3VT), there is also FTP access via the Online Data Access (ODA) that allows you to access both datasets and mini-files (small, extracted, areas of interest).

For further details please contact the EUMETSAT User Helpdesk.

6.3 User Products Dissemination Concept

This Document is Public

All Sentinel-3 products are disseminated in Product Dissemination Units (PDUs) to ease the online dissemination and data handling for the users. The PDU is a slice of data and is defined per product type. Three kinds of PDU are defined for Sentinel-3 products:

1. A **frame** is identified by means of a fixed reference system based in along track coordinates and along orbit cycle coordinate. The along-track coordinate identifies the product frame start point with respect to a fixed orbit position (like the ANX). Each frame is stepped by a constant time interval along the orbit track. The along orbit cycle coordinate identifies the relative orbit number within the orbit cycle.

SLSTR NRT/NTC L1 RBT and NRT L2 WCT and WST products are distributed as frames.

2. A **stripe** coincides either with the acquisition dump or with a defined acquisition time segment whose length may differ according to the instrument type.

SLSTR NTC L2 WCT and WST products are distributed as stripes

3. **Tiles** are defined only for Vegetation-like 1 or 10-day synthesis products, VGT-S1 (SY_2_VG1) and VGT-S10 (SY_2_V10), provided on a Plate Carrée map projection.

6.4 Software Tools

6.4.1 Sentinel-3 Toolbox

The Sentinel-3 Toolbox consists of visualisation, analysis and processing tools for the exploitation of OLCI and SLSTR data, and is an extension to the SeNtinel Application Platform (SNAP) that can be downloaded from the Science Toolbox Exploitation Platform (STEP)².

Once SNAP has been downloaded and installed it is possible to open L1 and L2 SLSTR products. If you need questions answered about the SNAP tool and associated Sentinel toolboxes then there's an on-line forum³.

6.4.1.1 Installing the toolbox

In case you haven't already done so, click/double-click the installer and follow the on-screen instructions to install SNAP.

6.4.1.2 Opening a Sentinel-3 product

Sentinel-3 products are provided not as single files but as a collection of files contained within a folder. The folder name is the actual product name, ending with “.SEN3”. Each folder contains a

² STEP download page: <http://step.esa.int/main/download/>

³ step forum: <http://forum.step.esa.int/>

This Document is Public

metadata file named xfdumanifest.xml and at least one NetCDF file. Each NetCDF file contains a subset of a Sentinel-3 product's content.

To open a Sentinel-3 product, you can either:

- Drag and drop the whole folder into the "Products View"
- Drag and drop the xfdumanifest.xml-file into the "Products View"
- Choose "File->Open Product", navigate to the xfdumanifest.xml file and click "Open Product"
- Choose "File->Import Raster Data->Multispectral Data->SENTINEL-3", navigate to the xfdumanifest.xml file and click "Open Product"

You can also open single NetCDF files. However, keep in mind that these will only show a part of the Sentinel-3 product and, in most cases, lack geocoding.

For a video example (for OLCI – but the same principles apply for SLSTR) please see the following video from EUMETSAT Training Manager:

<https://www.youtube.com/watch?v=DibAtfHoc6U>

When opening an SLSTR Level 1 RBT product you will be prompted as to which resolution you wish to open:

- 500 m: Will open an RBT product and display both the 500 m and 1 km bands; the 1 km bands are sub-sampled onto the 500 m grid;
- 1 km: Will open an RBT product and display the 1 km bands only (you will not be able to access bands S1 to S6).

6.4.1.3 Basic functionality

Once you have opened a product in SNAP there are many different things you can do next. Here are some basic activities:

- Displaying a colour composite: choose "Window->Open RGB Image Window".
- Displaying spectra, choose "Optical->Spectrum View".
- Displaying flags/masking the data: using the Mask Manager.
- Displaying uncertainty information, see the Uncertainty Visualisation tool window present in the bottom left.

This Document is Public

6.4.2 View the contents of a NetCDF file?

If you want to browse the detailed contents or metadata of a NetCDF file (as opposed to visually looking at and interrogating the array in SNAP) then there are interactive tools such as Panoply⁴ alongside Linux commands such ncdump.

6.4.3 Cerbere and Felyx

More advanced users may wish to use Cerbere and Felyx. Felyx is a free software solution, written in python and JavaScript, whose aim is to provide EO data producers and users with an open-source, flexible and reusable tool to allow the quality and performance of data streams (satellite, in situ and model) to be easily monitored and studied. For more information please consult the Felyx User Guide:

http://felyx.readthedocs.io/en/latest/user_guide.html

In addition to Felyx is the Cerbere, free and open source python modules for the reading, interpretation, and writing of (primarily ocean) geophysical data, including Sentinel-3. For further information visit the Cerbere pages at:

<http://cerbere.readthedocs.io/en/latest/>.

An example for reading SLSTR data is given at:

http://cerbere.readthedocs.io/en/latest/recipes/reading_s3_slstr.html

.

⁴ Panoply download: <https://www.giss.nasa.gov/tools/panoply/>

7 DATA QUALITY

A summary of all known product issues is provided in the product notices. These can be found on the EUMETSAT web pages at:

<https://www.eumetsat.int/website/home/Data/CopernicusServices/Sentinel3Services/SeaSurfaceTemperature/index.html>

Routine reporting of SLSTR data quality is provided in the SLSTR Cyclic Report. These are generated every cycle (roughly every 27 days or 501 orbits) and can be downloaded from:

<https://sentinel.esa.int/web/sentinel/technical-guides/sentinel-3-slstr/data-quality-reports>.

Validation results from comparisons to drifting buoys show that the difference between SLSTR and drifting buoys is given in Table 3.:

Retrieval	Quality Level	Number of matchups	Median (K)	Robust Standard Deviation (K)
N2	5	692	-0.19	0.28
N2	4	5413	-0.21	0.41
N2	3	1172	-0.21	0.73
N2	2	110	-0.21	0.95
N3	5	4956	-0.18	0.25
D2	5	729	-0.20	0.29
D2	4	4804	-0.13	0.31
D2	3	179	-0.10	0.42
D3	5	3163	-0.12	0.26

Table 3: SLSTR validation against drifters

These results compare SLSTR SST_{skin} to drifter SST_{depth}. The SSES_bias field has not been applied to the results. A wind speed filter of 6 ms⁻¹ has been applied to remove all match-ups below this wind speed. A median difference of -0.13 K is expected for this type of comparison.

Users are advised to use:

- Only D2 and D3 SSTs
- Only quality level = 5 at night time and quality level ≥ 4 at daytime

For users who wish to use the nadir-only retrievals – N2 and N3 – you are advised to only use data where the satellite zenith angle is < 55 degrees.

8 USER BEWARE!

This section contains details of SLSTR specific features that you should be aware of.

8.1.1 Product Grids in RBT and WCT Products

Two grids are defined for SLSTR outputs: the measurement grid, also called instrument reference grid, and a raster image grid. Each grid contains several variations according to the different instrument view and resolution. For operational reasons, all SLSTR L1 and L2 files are defined on the image grid. However, the products contain the required information to reconstruct the instrument grid if necessary.

The instrument grid is the native grids on which the SLSTR collects data as it scans. A scan number identifies the number of the scan line, starting at the ANX (point at which the satellite crosses the equator from South to North). A pixel number identifies the pixel count of any scan. A detector number then maps, for each pixel, the row and the column number (aligned with the along track and across track directions) onto a two-dimensional matrix of detectors. The image grid is locally Cartesian and is aligned with the sub-satellite track. All data are provided on this grid to provide raster "image-like" data.

A lower resolution tie-point grid is also defined, and annotations such as meteorological or viewing geometry data are provided on this grid. It is aligned with the 1 km and 0.5 km image grids and is regular in distance across track (16 km) and regular in time along track (1 km).

8.1.2 Aligning the product grids in RBT and WCT Products

To correctly use the three grids together (for RBT and WCT users only) you need to find the offsets of the three grids relative to each other. This information (known as *track_offset*) can be found in either the manifest file or in the datasets. An example of the three product grids for one granule is shown in Figure 5, which plots the geodetic coordinates for the tie-point grid in blue, the nadir grid in green and the oblique grid in red. Also, shown with the black line in the centre of the oblique view is the location of the SSP.




Figure 5: (Left) Example SLSTR product grids showing the tie-point (blue), nadir (green and oblique (red) geodetic coordinates. The SSP is indicated by the black line.

The tie-points are spaced every 16-km across-track and every 1-km along-track; the nadir and oblique grids are spaced every 1-km in both along-track and across-track dimensions. To use the

This Document is Public

grids together you must first interpolate any data on the tie-point grid in the across-track dimension to the same resolution as the measurement grids. Then, using the track-offsets, you can align all three grids to the SSP.

8.1.3 Mixed SST fields in WST Product

The SLSTR Level 2 WST product contains the best SST for each location across the swath. Please use the experimental field “sst_algorithm_type” to discriminate between the various retrievals (N2, N3, D2 or D3). An example is shown below in Figure 6.




Figure 6: (Left) Full swath WST SST image and (right) “sst_algorithm_type” showing the dual-view (cyan) and nadir-only (purple) regions.

For reference work, we advise users to only use dual-view (D2 or D3) SSTs.

8.1.4 Quality level and SSES in WST Product

The SLSTR Level 2 WST files contain the standard GHRSSST SSES and quality level fields. For reference use we advise users to only use data of quality level 4 and above (and only dual-view SSTs – see previous sub-section).

8.1.5 Data over all water bodies in WCT and WST Products

The SLSTR Level 2 WCT and WST products contain SST over inland water bodies. An example is shown below in Figure 7.




Figure 7: SLSTR SST image of the Amazon estuary in South America showing the scale of inland water bodies provided in SLSTR data.

For WCT users:

This Document is Public

- If you do not wish to use inland water bodies in your analysis or conversely only wish to use inland water bodies then please use the confidence flags.

For WST users:

- If you do not wish to use inland water bodies in your analysis or conversely only wish to use inland water bodies then please use bits 3 (lakes) and 4 (rivers) of the “l2p_flags” variable to distinguish them

8.1.6 NeDT in WST product

The SLSTR Level 2 WST products contain estimates of the NeDT for the nadir-only BTs recorded in the three IR channels. An example is shown in Figure 8. Small pixel to pixel variability is clearly seen in Figure 8 owing to the instrument design. Each of the three IR channels has two detectors, with S8 and S9 also having two integrators. Consequently, a checkerboard pattern is seen that varies every 20 rows, corresponding to the calibration averaging window used to calculate the gains and offsets for each detector. NeDT will also vary with scene temperature – the underlying large scale structure seen in Figure 8.




Figure 8: Example NeDT image for channel S8

8.1.7 Using flags in RBT and WCT Product

The SL_1_RBT and SL_2_WCT products have several annotation datasets to help interpret the measurement data. The most used file will be the product quality flags, which are provided for each measurement grid and view combination. In this file are a set of masks summarising the location of the pixels, the basic cloud mask and instrument errors.

The location of the pixel and a summary cloud flag can be found in the confidence variable. Bitmask. The content is listed below in Table 4.

This Document is Public

Bit	Mask name	Meaning if set
0	coastline	Coastline in field of view
1	ocean	Ocean in field of view
2	tidal	Tidal zone in field of view
3	land	Land in field of view
4	inland_water	Inland water in field of view
5	unfilled	Unfilled pixel (1 if this pixel is never tested or filled)
6	spare	spare
7	blanking_pulse	RADAR active
8	cosmetic	Cosmetic fill pixel
9	duplicate	Pixel has a duplicate
10	day	Pixel in daylight
11	twilight	Pixel in twilight
12	sun_glint	Sun glint in pixel
13	snow	Snow
14	summary_cloud	Summary cloud test
15	summary_pointing	Summary pointing

Table 4: SLSTR confidence bitmask

For example, to check if a pixel has been classified for land then you check to see if bit 3 has been set; for the summary cloud flag, you check if bit 14 has been set.

For users who wish to look at the individual cloud tests rather than use the summary flag then these are provided in the cloud variable. The content of the cloud variable is given in Table 5.

Bit	Mask name	Meaning if set
0	visible	Visible channels cloud test
1	1.37_threshold	1.37 threshold test
2	1.6_small_histogram	1.6 μm small-scale histogram test
3	1.6_large_histogram	1.6 μm large-scale histogram test
4	2.25_small_histogram	2.25 μm small-scale histogram test
5	2.25_large_histogram	2.25 μm large-scale histogram test
6	11_spatial_coherence	11 μm spatial coherence test
7	gross_cloud	12 μm gross cloud test
8	thin_cirrus	11 μm /12 μm thin cirrus test
9	medium_high	3.7 μm /12 μm medium/high level test
10	fog_low_stratus	11 μm /3.7 μm fog/low stratus test
11	11_12_view_difference	11 μm /12 μm view difference test
12	3.7_11_view_difference	3.7 μm /11 μm view difference test
13	thermal_histogram	11 μm /12 μm thermal histogram test
14	Spare	spare
15	spare	spare

Table 5: SLSTR cloud bitmask

This Document is Public**8.1.8 Converting from Brightness Temperature to Radiance in RBT Product**

The BT measurements provided by SLSTR are integrated spectral radiances across the range of the spectral filters used in each of the spectral bands, S7, S8 and S9. These can be converted to a measure of the integrated radiances by inverting the radiance to BT look up tables.

To do this a user must:

1. Obtain the radiance to BT look up tables:

These are Auxiliary Data Files (ADF) with a filename like:

S3A_SL_1_**N****S8**AX_20000101T000000_20991231T235959_20151214T120000_____
_____.MPC_O_AL_001.SEN3

N is the view it can be either N for nadir or O for oblique

S8 is the spectral channel

2. Read the radiances and temperatures variables

The file contains an array of temperatures and the radiance to temperature lookup table.

3. Interpolate the radiances for the BT at each pixel.

8.1.9 Converting from Radiance to Reflectance in RBT Product

The SLSTR shorter wavelength channels (S1 to S6) provide measurements of TOA radiances in units of $\text{mW m}^{-2} \text{sr}^{-1} \text{nm}^{-1}$. These values are often not useful when comparing or merging data from multiple sensors as they invariably have different sun angles at the time of measurement and different spectral profiles.

A more useful unit to compare sensors is normalised reflectance, which can be generated from the radiance using the following formula:

$$\text{reflectance} = \text{PI} * (\text{ToA radiance} / \text{solar irradiance} / \text{COS}(\text{solar zenith angle}))$$

Note: You must use the solar irradiance at TOA from the “quality” dataset for the respective channel.

8.1.10 Range of valid brightness temperatures in channels S7, S8 and S9

The BT limits (BT_min and BT_max) for S7, S8 and S9 are the cut-off in the processor outside of which the flags are set for invalid radiance. The current values are:

- S7: 150 - 305 K
- S8: 150 - 350 K
- S9: 150 - 350 K

The actual limits possible from the detector dynamic range modify these in the following way:

This Document is Public

- S7: values can fill all of BT_min – BT_max range but accuracy drops off sharply below 215 K. The counts-to-BT conversion in the lower end is essentially flat, so a change of 1 count results in a large change in BT, which results in very large rapid jumps in BT below 200 K.
- S8: lower limit currently set to approximately 198/200 K (depends on which of 2 detectors is used) - below that, no-signal flag set. Upper limit currently approx. 347 K (above that saturation flag set). Work to lower BT_min towards 184 K is ongoing.
- S9: values can fill all of the BTmin to BT_max range.

The information in this section was provided by Ed Polehampton (STFC RAL Space) as part of the Sentinel-3 Mission Performance Centre (MPC) SLSTR Expert Support Laboratory (ESL).