

Cees J. van Westen<sup>(1)</sup>, Saibal Ghosh<sup>(2)</sup>, Pankaj Jaiswal<sup>(2)</sup>, Tapas Ranjan Martha<sup>(3)</sup> and Sekhar Lukose Kuriakose<sup>(4)</sup>

# From landslide inventories to landslide risk assessment; an attempt to support methodological development in India

- (1) Faculty of Geo-Information Science and Earth Observation (ITC), University of Twente, 7500 AE, Enschede, P.O. Box 217, The Netherlands. E-mail: westen@itc.nl
- (2) Geological Survey of India, Kolkata, India
- (3) National Remote Sensing Center, Hyderabad, India
- (4) Centre for Earth Science Studies, Trivandrum, India

Abstract India is now housing 17% of the world's population. Landslides are an increasing concern in India due to the rapid population expansion in hilly and mountainous terrain. Landslides affect vast areas within India, in particular in the Himalayan chain in the North and Eastern part of the country and the Western Ghats in the Southwest. The Geological Survey of India (GSI) has been designated as agency responsible for landslide inventory, susceptibility and hazard assessment. Until recently their landslide susceptibility assessment was based on a heuristic approach using pre-defined weights or ranking of geofactors, following guidelines of the Bureau of Indian Standards (BIS). However, this method is disputed as it doesn't always provide accurate results.

This paper gives an overview of a recent research project between GSI, the National Remote Sensing Centre (NRSC) and ITC (the Netherlands) on how the existing methods for landslide inventory, susceptibility and hazard assessment in India could be improved, and how these could be used in (semi)quantitative risk assessment. Due to the unavailability of airphotos in large parts of India, satellite remote sensing data has become the standard data input for landslide inventory mapping. NRSC has developed an approach using semi-automatic image analysis algorithms that combine spectral, shape, texture, morphometric and contextual information derived from high resolution satellite data and DTMs for the preparation of new as well as historical landslide inventories. Also the use of existing information in the form of maintenance records, and other information to generate event-based landslide inventories is presented. Event-based landslide inventories are used to estimate the temporal probability, landslide density and landslide size distribution.

Landslide susceptibility methods can be subdivided in heuristic, statistical and deterministic methods. Examples are given on the use of these methods for different scales of analysis. For medium scales a method is presented to analyze the spatial association between landslides and causal factors, including those related to structural geology, to select the most appropriate spatial factors for different landslide types, and integrate them using a combination of heuristic and multivariate methods. For transportation corridors a method is presented for quantitative hazard and risk assessment based on a nearly complete landslide database. Deterministic methods using several dynamic slopehydrology and slope stability models have been applied to evaluate the relation between landuse changes and slope stability.

The susceptibility maps can be combined with the landslide databases to convert them into hazard maps which are subsequently used in (semi) quantitative risk assessment at different scales of analysis.

**Keywords** landslides, India, landslide inventory, susceptibility, hazard, risk assessment

#### Introduction

Landslides are significant hazards that can be disastrous to human life and property. Recent global landslide assessment studies (Petley et al., 2005; Nadim and Kjekstad, 2009; OFDA/CRED, 2010) reveal that the countries with the highest risk to landslides are mostly in the developing world.

About 15% of India (~0.49 million km<sup>2</sup>) including the mountain areas of the Himalayas, the Meghalaya plateau, and the Western Ghats are landslide-prone (NDMA, 2009). During the monsoon, those areas witness frequent landslide events triggered by rainfall. Many landslide-prone areas also belong to the maximum earthquake-prone areas in India (BIS, 2002), where earthquakes of Modified Mercalli intensity VIII to IX can occur, and thus, are also susceptible to earthquaketriggered landslides.

To mitigate the effects of such disasters, the Government of India has enacted the National Disaster Management Act in 2005. This act aims at adopting proactive and multidisciplinary approaches towards achieving disaster awareness and mitigation. The policy stresses that investments in disaster-preparedness and mitigation are much more cost-effective than expenditures on relief and rehabilitation (NDMA, 2009). In this regard, predictive maps of landslide hazard, preferably at medium scales (1:25,000 to 1:50,000) are vital geo-information products that administrators/planners can use in formulating regional mitigation plans for landslide disasters. The aim of using medium-scale landslide hazard maps is to draft proper land-use zoning regulations in landslide-prone areas to alleviate, if not prevent potential loss of human life and damage to property.

Landslide research in India has always been hampered by the lack of data. In the border zones of the country, including the entire Himalayan range the use of topographical maps and airphotos has been restricted for security purposes. Thus the generation of landslide inventory maps has always been a major problem. However, due to the availability of India's own system of Earth Observation satellites, high-resolution remote sensing data (e.g. Recourcesat-1 LISS-IV, Cartosat) has become the standard input data for landslide inventory mapping, and for the generation of Digital Elevation Models used in landslide studies.

Up to now there are very few examples in India of landslide hazard maps (Sarkar and Kanungo, 2005; Bhandari, 2006; Sharda, 2008), although a substantial part of the country's most landslide-prone area is now covered by medium-scale qualitative landslide susceptibility maps (BMTPC, 2003). The Bureau of Indian Standards has formulated guidelines, among others, for landslide susceptibility zonation on a medium scale (1:50,000) (BIS, 1998), using an expert-based indirect weighting approach (Anbalagan, 1992). The method uses pre-defined weights or ranking of geofactors without directly or indirectly considering the landslide inventory data. There have been discussions on the improvement of this method, and the inclusion of landslide inventories combined with GIS-based statistical analysis as an alternative for medium scale susceptibility assessment (Sharda, 2008; NDMA, 2009)

In 2006 a joint research agreement was made between the Geological Survey of India (GSI), the National Remote Sensing Centre (NRSC; Department of Space, Government of India) and the Faculty of Geo-Information Science and Earth Observation (ITC), University of Twente, The Netherlands. The agreement focused on the development of training courses and the implementation of joint research projects. The Geological Survey of India (GSI) has been designated as the nodal agency for landslides by the Indian government. The National Remote Sensing Center (NRSC) under the Indian Space Research Organisation (ISRO) is in charge of rapid damage assessment, and in (landslide) inventory mapping and susceptibility assessment, using the suite of India's own satellites. The research collaboration included two PhD researchers from GSI and one from NRSC. Later also other organizations were involved in the

research. Another PhD researcher from the Centre for Earth Science Studies (CESS), in Thiruvananthapuram, Kerala, was integrated in the project, as well as one from the Indian Institute of Remote Sensing (IIRS), which is the training centre of the Indian Space Research Organization. The research collaboration also involved a number of European institutions, such as the Faculty of Geosciences of Utrecht University (The Netherlands), the National Research Council of Italy (CNR-IRPI, Perugia), the University of Vienna, and the German Geological Survey (BGR, Hannover).

The main objective of the research project was to develop and test methods for landslide inventory mapping, susceptibility-, hazard- and risk assessment that are applicable in India, considering the variability and complexities of the landslide-prone terrains, and considering the data availability. Methods were developed for different scales of analysis. The methods focused on techniques for generating landslide inventories, the application of appropriate susceptibility models (heuristic, statistical, physically based), the characterization of landslide hazard in terms of temporal, spatial and size probability, and the use of this information in landslide risk analysis.

#### **Study areas**

It was decided to develop and test the methodology in four different areas in India, each one linked with a PhD research. Figure 1 shows the location of the 4 study areas.



Figure 1 National landslide susceptibility map (Rajarathnam and Ganapathy, 2006) with the location of the test sites. A: Okhimath (Uttarakhand state), B: Kurseong (Darjeeling/West Bengal states); C; Tikovil (Kerala state), D: Nilgiri (Tamilnadu state.

Each of the four studies had its own main research focus, as can be seen from Table 1.

Table	1:	Main	research	themes	in	the	four	case	study	areas,
indica	ted	in Fig.:	1.							

Area	Research focus					
A: Okhimath	Detection of landslides by object - oriented					
& Uttarkashi	image analysis. Generation of Digital Surface					
(Uttarakhand)	Models from Cartosat satellite images; application of					
	NDVI-based thresholds for landslide detection;					
	development of a rule set for removal of false					
	polygons; semi-automatic classification of landslide					
	types; development of a method for landslide					
	detection from multi-temporal panchromatic					
	images; bivariate statistical analysis; and semi-					
	qualitative risk analysis (Martha et al., 2011d; Das et					
	al., 2010, 2011)					
D: Kurseong	Knowledge guided empirical prediction of					
(Darjeeling /	landslide hazard. Landslide inventory made					
West Bengal)	through multi-temporal image interpretation; event-					
	based landslide inventories; relation with triggering					
	rainfall; analysis of the structural control of					
	discontinuities on rock slides; combination of					
	heuristic and statistical methods for susceptibility					
	assessment; temporal- spatial- and size frequency					
	analysis; semi-quantitative risk analysis (Ghosh et					
	al., 2011d)					
C: Tikovil	Physically - based dynamic modelling of the					
(Kerala)	effect of land use changes on shallow landslide					
	initiation. Inventory made with community-based					
	mapping; detailed soil thickness modelling;					
	geotechnical and hydrological characterization;					
	ground water modelling; slope stability analysis;					
	failure probability analysis; runout modelling;					
	prediction of future slope stability scenarios					
	(Kuriakose et al., 2010)					
D: Nilgiri	Landslide risk quantification along					
(Tamilnadu)	transportation corridors based on historical					
	information. Landslide inventory made from					
	maintenance records for road and railroad; rainfall					
	threshold analysis; frequency-size analysis; hazard					
	analysis; quantitative direct and indirect risk					
	analysis; use of risk information for disaster risk					
	reduction (Jaiswal et al., 2011c)					

In the following sections the main results from these four studies will be presented.

### Case study A: Landslide inventory using Object Oriented Image Analysis

Landslide inventories that span a substantial period of time are one of the key requirements for landslide studies (Van Westen et al., 2008). Image interpretation still is the main method for generating these. Several research attempts have been made to automate and speed up the process of landslide interpretation as major trigering events might cause hundreds or even thousands of landslides. Since pixel-based methods have not produced accurate results for sufficiently detection and classification of landslides, object-oriented analysis (OOA) which imitates the human interpretation process in identification of landslides, has emerged as a good alternative due to its inherent ability to incorporate additional information layers such as digital terrain models (DTMs) and thematic maps in the analysis. Furthermore, as landslides are geomorphic processes, their characterisation in different types mostly relies on contextual criteria, which can best be described by objects obtained from segmenting the digital image into spatially cohesive regions/objects rather than pixel values. Martha et al. (2011d) developed semi-automatic image analysis algorithms that combine spectral, shape, texture, morphometric and contextual information derived from high resolution satellite data and DTMs for the preparation of landslide inventories. The main innovative aspect of the research lies in the selection of landslide diagnostic parameters and their use in the comprehensive characterisation of different types of landslides, a concept which is addressed for the first time detection of landslides in an object-based for environment.

DTM accuracy is an important factor since its morphometric derivatives, such as terrain curvature, slope, and flow direction, contribute to the successful detection and classification of landslides. Cartosat-1 along-track stereoscopic data, which are provided with Rational Polynomial Coefficients (RPCs) for block triangulation, were used to create a DTM with 10 m grid size (Martha et al., 2010a). Conversion of a DSM to a DTM was carried out for calculating landslide volume and terrain morphometric parameters, by subtracting vegetation height from the DSM. The landslide volume extracted from pre- and post-landslide DTMs (Fig. 2) without control points matched well with volume extracted from the DTMs with control points, indicating that a field survey for control points is not a strict requirement (Martha et al., 2010b). It also showed that landslide volume information can be derived only with RPCs, if both pre- and post-image pairs can be brought into the same relative reference framework.



Figure 2 Volumetric analysis of the Salna landslide based on satellite derived DTMs. (a) elevation difference due to the landslide with negative values showing lowering of surface and positive values showing rising of the surface after the event, and (b) extent of the volume loss and volume gain, which corresponds to the zones of depletion and accumulation, respectively (Martha et al., 2010b).

A set of approaches was developed that exploit the object properties extracted using a region-growing segmentation of multispectral Resourcesat-1 LISS-IV Mx (5.8 m) image (Martha et al, 2010c). The method was tested in the Okhimath area, in Uttarakandh state. An algorithm comprising 45 individual routines, such as controlled segmentation, merging and classification was developed using eCognition software, which detected 42 major and minor landslides in an 80 km<sup>2</sup> area. The algorithm, initially extracts landslide candidates using an NDVI threshold, and subsequently false positives were eliminated from the landslide candidates using spectral, texture, shape and contextual criteria (Fig. 3). Landslide classification was done using terrain curvature and contextual criteria, and five different types of landslides were identified. The object-based classification, when compared with a landslide inventory map prepared by stereoscopic photo-interpretation and detailed field check, resulted in a detection accuracy of 76.4%, while 69.1% of the landslides were correctly classified in different landslide types. The results are considered to be good, since landslides are detected in an area dominated by false positives such as rocky barren land, uncultivated agricultural terraces and river sands. The minimum landslide size detected by the method was 700 m<sup>2</sup>.



Figure 3 Generalised methodology flowchart for semi-automatic detection of landslides using object-based methods (Martha et al., 2010c).

The algorithm developed required user-defined segmentation criteria to control the object size, which was considered a drawback in applying a fast and generic method for landslide detection and classification. Therefore, an objective method to optimise segments was developed subsequently (Martha et al., 2011a). Using spatial autocorrelation and intrasegment variance, a new plateau objective function (POF) was developed, which was used to determine the segmentation criteria for multi-scale analysis, essential for the detection of landslides and elimination of false positives. Another drawback of the originally developed algorithm was the use of manual thresholds for the elimination of false positives from landslide candidates. This was adjusted using a K-means clustering method. The improved algorithm, comprising of four sub-modules, resulted in a detection accuracy of 76.9% for the training area (Fig. 4)and 77.7% accuracy for a geomorphologically distinct validation area in Darjeeling. It not only increased the accuracy of detection but also reduced the overall error of commission.



Figure 4 Landslide types recognised using OOA in the Okhimath area. The dotted lines in insets (b) and (c) show the reference landslide inventory (Martha et al., 2011a)

Another algorithm was used for landslide detection from archived high resolution panchromatic images, which is a modified version of the second one. It uses a brightness threshold instead of NDVI to extract landslide candidates (Martha et al., 2011b). Local thresholds using contextual criteria showed better results than global thresholds, and allowed to identify small translational landslides within barren rocky land that are generally bright. To eliminate false positives, more texture measures, such as GLCM homogeneity and standard deviation, were used along with shape and contextual criteria. Finally, a multi-temporal annual landslide inventory for 13 years was prepared and used for the generation of a landslide susceptibility map with the help of a bivariate model (Martha et al., 2011c).

The final algorithm for the detection of landslides, developed by Martha et al. (2011d) is generic and requires two primary inputs (a satellite image and a DTM), and doesn't require information that should be collected in the field. The semi-automatic approach is flexible enough to address the spatial and spectral variability of landslides and false positives. The knowledge-based approach shows considerable improvement over previous pixel- and object-based methods of landslide detection in terms of the location, size and type of landslide. The method has increased the potential to rapidly generate event-based landslide inventories after major triggering events, within a short period of time. The method developed in this research has proven its value in several areas in the Indian Himalayas and could potentially contribute to the rapid detection of landslides in other susceptible areas.

## Case study B: Knowledge-guided empirical prediction of landslide hazard at the medium scale

Estimating and mapping variations in the spatial likelihood of occurrence of landslides (susceptibility assessment) is a fundamental step towards landslide hazard prediction. Landslide susceptibility aims to identify where future landslides are likely to occur, based on the fundamental assumption that spatial factors that caused present and past landslides are likely to cause similar landslides in the future.

In India, the BIS guidelines (BIS, 1998) recommended an indirect approach to landslide susceptibility mapping and provides a generalized heuristic system of predefined weighting or ranking of geofactors called landslide hazard evaluation factor (LHEF) rating. These LHEF ratings are applied irrespective of various terrain conditions and were determined by an expert group without directly considering the landslide inventory data. Since the spatial extents of landslide geofactors and their respective causal association with different types of landslides and failure mechanisms are variable, the fixed LHEF ratings assigned to geofactors can be inappropriate and lead to less accurate landslide prediction rates when applied to different areas. The aim of this research was to propose an effective method for medium scale landslide hazard and risk analysis suitable for the Indian geoenvironment which can be readily used by the public research Institutes/Organisations engaged in landslide research in India. The proposed method considered the variability and complexities of one of the predominant landslide-prone terrains in India (e.g., the Darjeeling Himalayas) and the landsliding processes prevalent there, so that the aspects of variable controls of landsliding factors can be better understood (Ghosh et al., 2009a; **2011d**). This was done through:

• Generation of landslide inventory maps for different triggering events, based on the available information in the forms of landslide maps, images and archives.

These maps should portray the landslide patterns and types of triggering events with a range of return periods, which can be used to analyse the temporal and magnitude probabilities (Ghosh et al., 2009b; 2011b);

- Development of an exploratory analytical technique for understanding the mutual/exclusive spatial relation between regional structures (e.g., faults/fractures) and slope aspects with rockslides of a certain type (Ghosh and Carranza, 2010);
- Development of a specific method for analyzing different rock slope failure modes, by spatially incorporating the 3-D structural orientation data (Ghosh et al., 2010);
- Analysis of the spatial associations between landslides of specific types and a set of causal factors, using bivariate statistical methods for selecting and weighting the appropriate spatial factors and integration of the right and weighted spatial factors into landslide susceptibility maps for each type of landslide (Ghosh et al., 2011a);
- Integration of the spatial, temporal and size probabilities of landslide events and conversion of the susceptibility maps into hazard maps (Ghosh et al., 2011b);

#### **Generating inventory maps**

The source data sets that were used in this study for landslide inventory mapping in an area of 90 km<sup>2</sup> consisted of high-resolution satellite images, aerial photographs, topographic maps, old landslide inventory maps and reports of field investigations which were available for the study area in Darjeeling. The oldest data set consists of topographic maps prepared by the Survey of India (SOI) in 1969, which included the locations of prominent and active landslides of a major triggering event in 1968. The next data set consists of 1:50,000 and 1:10,000 scale black-and-white stereo-air photos from 1980, which were interpreted using stereo-image interpretation. The third and fourth data sets are fieldbased landslide inventory maps from 1993 and 1998 prepared by GSI soon after major triggering events. For the period 2002 to 2006, three high-resolution Indian satellite images were used as source data. The most recent data set is a detailed landslide inventory map prepared during this research through field surveys soon after a recent landslide event in 2007. For each period a landslide inventory was made, and landslides were mapped as polygons, resulting in a total of six eventbased landslide inventories, which were compared to examine variations in landslide characteristics (frequency, area, density, type and activity) (Ghosh et al., 2011C). Unfortunately the available data was not covering all landslide triggering events in the last 50 years.

Therefore a multivariate classification technique (discriminant analysis, DA) was used to define an empirical relationship between days with and without landslide events as response variable and daily variation in rainfall amounts as predictor variables. The frequencies of landslide events predicted via DA that were linked to triggering rainfalls were then used in a Poisson distribution model to calculate the temporal probability of similar landslide events in the future, which were classfied in major, moderate and minor events (Fig. 5).



Figure 5 Threshold cumulative discriminant scores (DS) for predicted "minor", "moderate" and "major" landslide events. The available six events are shown and associated with corresponding inventory numbers to depict validity of modelderived severity classifications of known landslide events.

#### Rock failure type modelling

Many of the landslides in the Himalayas are rock slides, or are in weathering soil with a clear structural control. For rock slides, since failure propagates along a nearplanar surface (planar) or triggered along the intersection of two planes (wedge), the presence/ absence of any planar discontinuity, its nature, extent, orientation and frequency of occurrence in relation to topography are crucial deciding geofactors. The geometric or kinematic interrelationships between the attitudes of bedding/ foliation/ joint planes and topography are important in deciding the mode of movement of rock slides. To determine kinematically the unfavourable discontinuitytopography/ structure domains, different topographic segments were identified after establishing the geometric interrelationships of the orientations between topography and prominent discontinuity surfaces (Ghosh et al., 2010). For the calculation of the angular interrelationship, raster maps of topographic slope, topographic aspect, discontinuity dip and discontinuity dip direction were used. Dip and dip direction raster maps of prominent discontinuities were generated through interpolation of discrete dip/ dip direction values of foliation planes, measured at different point locations. After this structural domains were derived by combining the above four raster maps and calculating their angular relationships. Different rock slide failure mechanisms were successfully identified spatially by studying the kinematic interrelationships between the attitudes of distributed bedding/ foliation/ joint planes and topography through spatial correlation. A GIS-based application was used for the spatial analysis with distributed rock structure data (Günther, 2003) and areas susceptible to wedge, planar and toppling failure modes were delineated (Fig. 6). The best approach would be to parameterize all these structure domains per failure mechanism spatially and utilise them for a detailed quantitative rock slope susceptibility analysis.



Figure 6 Modelled unstable slopes for different types of rock slope failure (a) plane failure (b) wedge failure (c) topple failure (d) slopes where at least one failure mode is kinematically possible.

#### Combining heuristic and statistical methods

Heuristic methods for spatial prediction of landslide occurrence can either be direct or indirect. In indirect heuristic methods, individual factors are assigned specified weight values or ratings that are based on subjective criteria. The main limitations/problems of heuristic methods are related to the subjectivity involved. Although the same subjectivity could be present in selecting and mapping of the factors for data-driven methods, the relative importance of the factors is determined by more objective techniques. One of the main advantages of heuristic methods is that they can allow site specific and landslide type specific evaluations of the causal factors, and avoid the generalization that is often used in data-driven ones.

Landslide susceptibility is a function of two types of spatial associations: (1) spatial associations of individual spatial factors with known landslides of a certain type; and (2) relative importance of individual spatial factors with respect to one another in relation to those known landslide occurrences. Methods of bivariate empirical analysis can model only the first type of spatial association. In contrast, multivariate methods can model those two types of spatial associations simultaneously, but often include spatial factors that do not seem to have a direct relation with the landslide process and generally do not include expert opinion. Therefore an empirical method was developed for the analysis of spatial association at a medium-scale. The data used are presented in Table 2.

For each class of a categorical factor, the Yule's coefficient (Bonham-Carter, 1994) was used to quantify its spatial association with known occurrence of shallow landslides. Based on calculated values of Yc for every factor, a Landslide Occurrence Favourability Score (LOFS) was calculated per factor class. Distance distribution analysis (DDA) was used for measuring the spatial association of continous variables.

Table 2: Data sources, including methods of preparation/mapping of spatial factors of shallow landslides. Sh\_rs = shallow translational rockslides. Db rs = shallow translational debris slides.

Generic	Specific	Source data, scale or spatial resolution	Landslide type	
factor theme	factor	and method of mapping of factor	Directly related	Indirectly
Topography/ morphometry	Slope Aspect Curvature	DEM of 10 m $\times$ 10 m pixel resolution; automated mapping in GIS.		•
Lithology or slope material	Rock and soil type	Field data, information from existing geological maps (1:10,000 -1:50,000 scales)	Sh_rs, Db_rs	÷.
Depth to bedrock	Soil/overburde n thickness	Estimated using field data from 400 sites and linked to lithology map	Db_rs	•
Structure	Distance to major thrusts	Compiled from 1:50,000 and 1:25,000 geological maps; interpreted from high spatial resolution satellite imagery and stereo air-photos (1:50,000 and 1:10,000); ground-truthing in the field.	Sh_rs,	Db_rs
	Distance to faults/fractures	Interpreted from stereo-pairs of 1:10,000 and 50,000 B×W air-photos with limited ground- truthing in the field.	Sh_rs,	Db_rs
	Distance to kinematically unstable slopes	Determined using field data of rock discontinuity orientations and DEM-derived slope and aspect maps (Ghosh et al., in press)	Sh_rs,	Db_rs
Land-use/ land-cover	Land-use/ land-cover	Interpreted from 1:10,000 and 1:50,000 B×W air-photos and multispectral IRS LISS 4 MX imagery (5.8 m spatial resolution) with limited ground-truthing in the field.	Sh_rs, Db_rs	
Old rockslides	Distance to old rockslides (pre-1968)	Mapped from stereo interpretation of 1:10,000 scale B×W stereo air-photos of 1980.	Sh_rs, Db_rs	•
Hydrology	Contributing area upslope	DEM of 10 m × 10 m pixel resolution	Sh_rs, Db_rs	-
	Drainage density	DEM of 10 m × 10 m pixel resolution; digitized streams from 1:25000 topographic maps.		
	bistance to streams	streams from 1:25000 topographic maps.		

For the analysis of inter-predictor weights the analytical hierarchy process (AHP) was applied. Based on the spatial association analyses and the predictor weights derived via AHP, 14 out of 21 identified spatial factors for shallow translational rockslides were used and 12 out 22 spatial factors for shallow translational debris slides. To integrate the selected predictors of each type of shallow landsliding, the weighted multi-class index overlay method was applied (Fig. 7).



Figure 7 Schematic flow diagram with data, processes and steps for developing 4 different models of susceptibility to shallow landsliding. Model 1 and 3 are based on weighted multiclass index overlay, model 2 on the direct use of selected predictors and model 4 on stepwise backward logistic regression.

The results were compared with a backward stepwise Logistic Regression analysis, which starts with all input predictors and ends with only statistically significant predictors that contribute to the prediction or classification.

The resulting susceptibility map was combined with the landslide inventories for different types of triggering events (major, moderate and minor), which were used to estimate temporal and spatial probability and to convert them into a hazard map, which was subsequently used in a semi-quantiative risk assessment (Ghosh et al., 2011b).

### Case study C: Physically based landslide hazard assessment

The third case study focused on the application of deterministic modelling at local scale, and to use it to evaluate the effect of environmental changes on landslide activity. The case study area is in the highland region forming the western slopes of the Western Ghats of Kerala state, which is increasingly affected by shallow landslides and debris flows. High intensity rainfall, and the presence of perched water tables resulting in high pore-water pressure conditions are considered as the principal trigger of these landslides. The spatio-temporal probabilities of shallow landslide initiation in this area are dependent on the land use which in turn determines the mechanical and hydrological effects of vegetation on slope stability. The application of physically-based spatially distributed modelling was the most suitable approach to verify this hypothesis as it has the capability to not only estimate the spatio-temporal probabilities of shallow landslide initiation, but also quantitatively assess the influence of changes in environmental conditions on slope stability, for example those of land use changes.

Four shallow landslide initiation models were applied, namely SHALSTAB, SINMAP, TRIGRS and STARWARS+PROBSTAB (Kuriakose et al., 2010). The STARWARS (Storage and Redistribution of Water on Agricultural and Revegetated Slopes) + PROBSTAB (Probability of Stability) model, which is a coupled hydrology and stability model that uses a first order second moment approach for quantifying the probability of failure, was identified as the most suitable for this research. A pilot study conducted in the upper Tikoy river basin (55 km<sup>2</sup>) revealed that it was necessary to accurately measure and spatially parameterize root reinforcement, soil depth, soil hydraulic conductivity and soil strength properties to derive reliable results from the model (Kuriakose et al., 2008). It was also evident that a detailed characterization of rainfall patterns and corresponding slope hydrological responses such as transient ground water level and discharge was necessary to calibrate and validate the STARWARS (the hydrology model) while a detailed landslide inventory was needed for the calibration and validation of PROBSTAB (the slope stability model).

To acquire hydrological data with a high temporal resolution, 13 automated open stand pipe piezometers, one discharge station (stage gauge) and one weather station were deployed in the Aruvikkal catchment from May 2007 onwards. A partially complete landslide inventory was prepared based on governmental reports, newspaper clips, field work and community-based approaches. Time series analysis conducted on the rainfall and the corresponding hydrological responses revealed that the slope hydrology of the catchment exhibits very rapid response to rainfall; the discharge of the catchment will respond within 1 hr. The average time necessary for a significant response of the perched water level to rainfall was 6 hrs while during the peak rainv season this lag may reduce to less than 1 hr. It was also observed that continuous and high intensity rainfall of about 4 hrs may cause a steep rise in the perched water table up to critical levels in regolith filled bed rock depressions and the persistence of this level for ~10 hrs may lead to shallow landslides in the catchment. Thus to capture the hydrological responses that lead to shallow landslide initiation in the catchment, the hydrology model should be able to predict these responses with a temporal accuracy of at least 6 hrs which necessitates the model time step to be of at least ihr in resolution.

All soil mechanical properties necessary were measured and spatially parameterized. Block regression kriging with altitude, aspect, slope, distance from streams, compound terrain index, curvature and land use as predictors was identified as the 'best' predictor of soil depth in such anthropogenic landscapes (Kuriakose et al. 2009b). Depending on the dominant plant species in each land use unit and the soil depth the corresponding root reinforcement applicable was derived from measured root tensile strength, pull out strength, root diameter and root density data. Nine species of plants were tested of which Teak (Tectona grandis) trees offered the highest amounts of net root reinforcement (Kuriakose and Van Beek, 2011). The STARWARS model was calibrated and validated against the observational data of 2007-2008 period. The PROBSTAB model was calibrated and validated against the landslide inventory of 2001 and 1993 respectively, for which the corresponding daily rainfall data available from a nearby tea estate was converted to hourly data using stochastic methods (Kuriakose et al., 2009a).

In order to evaluate the effects of long term and short term land use changes on slope stability in the region, historic (1913 to 2008) land use maps, soil depth maps and root reinforcement maps were derived. In addition the land use maps and corresponding root reinforcement maps of two future scenarios (2016 and 2058) were also derived. Although, these future land use scenarios represent only one of the many possible realizations, the interest in them lies in the fact that they show a possible scenario of reforestation, and hence conservation of the area. These data sets were used to simulate the corresponding slope stability and probability

8

of failure conditions based on the 1985 rainfall time series (disaggregated to hourly) which included the most extreme daily rainfall that has caused at least one shallow landslide in the study area in the past 57 years (Fig. 8).



Figure 8 Area with FOS<1 and the probability of failure corresponding to the land use scenarios of 1913, 1973, 2001, 2008, 2016, 2058 and the no-root cohesion condition (Kuriakose et al., 2010)

The land use changes from the pre-plantation (1913) scenario to present (2008) have resulted in an average increase in the potential area of failure by 43% and the spatio-temporal probability of failure by 49%. Despite setting up an idealistic land use scenario for the distant

future (2058), the overall slope stability did not revitalize to the pre-plantation period (1913) because the root reinforcement available was relatively lower as compared to the pre-plantation period.

The research showed that in the study area, the transition probability of land use change (and consequently the changes in soil depth and root cohesion) outweighs the rainfall quantity in determining the spatio-temporal probability of shallow landslide occurrence. This is in contradiction with the commonly held belief that the temporal probability of shallow landslides can be quantified with only the return probability of landslide-causing extreme rainfall events. Hence, transition probabilities of land use should be assessed and incorporated in regional scale landslide hazard assessments that utilize heuristic and stochastic techniques, especially in such anthropogenically modified terrains.

The study also analyzed the coupling of the initiation model with a runout model. A tentative scheme for coupling the results of STARWARS+PROBSTAB with a runout model named MassMov 2D (Begueria et al., 2009) is presented in Figure 9. By systematically varying the input variables based on a first order second moment approach (FOSM), one can derive the maximum, average and minimum extent of runout possible, given a certain initiation area and volume of material. Depending on the number of times that a given pixel gets affected by a debris flow, one can derive the spatial probability of being affected by a certain magnitude (depth, area or velocity) of debris flow, while the initiation model can provide the temporal probability of initiation of such a debris flow .



Figure 9 Scheme for coupling the results of STARWARS+ PROBSTAB with the runout model MassMov2D.

### Case study D: Landslide risk assessment along transportation corridors

The fourth case study focused on quantitative landslide risk assessment along transportation corridors (a road and a railroad) in the Nilgiri area (Tamilnadu), making use of a nearly complete historical database of landslide occurrences over the past 24 years (Jaiswal et al., 2011c).

#### Generation of landslide inventory from archives

In the Nilgiri area it was possible to generate a very detailed landslide inventory based on historical data. The records include railroad and road maintenance registers, and technical reports. From 1987 maintenance data were present in an analogue form recorded in a register. This register is updated soon after the occurrence of a landslide triggering event and is used for tendering contracts for (rail)road clearance. The technical reports include published and unpublished technical documents of landslide investigations. The data were used to reconstruct the landslide occurrences along the road and railroad over several decades. Data on 901 landslides were compiled from the historical records covering a 21 years period from 1987 to 2007. Figure 10 displays annual landslide maps from 1992 to 2007 (Jaiswal and Van Westen, 2011d).



Figure 10 Spatial distribution of landslides in different years along the railroad. Landslides are shown as points irrespective of their size.

The landslide dataset was used to analyze the landslide intensity for different years, by calculating the recurrence interval of the percentage of unit lengths of the road and railroad that would be interrupted during triggering events (Jaiswal and Van Westen, 2009).

To quantify landslide hazard using such a complete inventory, as was the case for the Nilgiri area, two essential parameters were assessed: the probability that landslides affecting the infrastructure are of a given magnitude, and total number of landslides per kilometer affecting the infrastructure in a given return period. The landslides in the study area were grouped in four magnitude classes ranging from I (less severe) to IV (catastrophic). The classification is essentially based on landslide type and volume but it also gives other characteristics such as the location of the source, damage potential and human perception about the risk related to landslides. The probability that a landslide affecting the infrastructure is of a given magnitude class was estimated using magnitude-frequency relationships. Annual probability of landslide occurrence was estimated from the observation of the frequency of past landslide events, by determining the annual exceedance probability (AEP), using Poisson and Binomial distribution models. The estimation of landslide risk, particularly indirect risk resulting from the blockage of transportation line, requires estimation of the number of landslides reaching the infrastructure per year. The number of landslides is required to calculate the blockage period based on clearance time needed per cubic meter of debris. The relation between the annual probability of occurrence of landslides (or return period) and the number of landslides of a magnitude class per kilometer was established using a Gumbel extreme value distribution (Jaiswal et al., 2010a).

Logistic regression analysis was carried out to model the susceptible areas to landslides on natural slopes. Rainfall threshold analysis was used to estimate the temporal probability of landslides, and magnitudefrequency analysis to obtain the probability of landslide size. These data were combined in an analysis of landslide initiation hazard on cut and natural slopes (Jaiswal et al., 2010a). Landslide run-out analysis was carried for landslides on natural slopes. Landslide vulnerability was established for landslides with different magnitudes and for different elements at risk. Landslide hazard and risk estimation was done using landslide events that occurred between 1987 and 2007 and the results were validated using landslides that occurred in 2008 and 2009. As a final output direct risk was quantified for properties (alignments, vehicles, buildings, and plantations) and people (commuters and residents) and indirect risks due to the traffic interruption (Jaiswal et al., 2010b; 2011a, 2011b) (See Fig. 11).

The results provided a quantitative estimate of total annual landslide losses, expressed in monetary value (US\$) for properties (Fig. 12) and in annual probability of death for people. An F-N curve was used to express the societal risks. The results are of important societal value and will provide inputs for planning risk reduction strategies, for developing risk acceptance criteria and for financial analysis for possible damage in the study area. The methodology provides a cost-effective approach to estimate direct and indirect landslide risks. The methods can be applied elsewhere if a similar historical landslide data set is made available.



Figure 11 Flow diagram showing the process adopted for landslide risk analysis (Jaiswal et al., 2010b).



Figure 12 Risk curve for total landslide losses in the study area (maximum risk) expressed in monetary value (US\$) (Jaiswal et al, 2011).

The research also presented the perception of Nilgiri people to landslide risk and the use of the obtained hazard and risk information in reducing landslide risk to the society.

#### Conclusions

The joint research programme between GSI, NRSC and ITC, in which also other Indian organizations were involved (IIRS and CESS) resulted in five PhD thesises, (Kuriakose et al., 2010; Ghosh et al., 2011d, Jaiswal et al., 2011c; Martha et al., 2011d; Das et al., 2011) and over 20 publications in scientific journals. The defence of 4 of the researchers was integrated with a symposium on landslide hazard and risk assessment in India, which was held on 4 and 5 July 2011 (See Fig. 13) in ITC, The Netherlands. The results will also be presented in a workshop in November 2011 in Hyderabad, India, during which further steps towards the development of improved guidelines for hazard and risk assessment in India will be discussed.



Figure 13 Participants of the symposium on Landslide hazard and risk assessment in India, held in ITC on 4 and 5 July 2011.

#### **Acknowledgments**

This research was carried out under the collaboration agreement between the Geological Survey of India (GSI), the National Remote Sensing Centre (Indian Space Research Organisation) and the United Nations University – ITC School for Disaster Geo-Information Management, University of Twente, the Netherlands.

We acknowledge the contribution of the following researchers, who collaborated in some way to the project (e.g. through joint field campaigns, training courses, image interpretation, modelling and discussions): Mauro Cardinali, Paola Reichenbach, Mauro Rossi and Fausto Guzzetti (CNR-IRPI); Andreas Günther (BGR); John Carranza, Norman Kerle, Victor Jetten and Alfred Stein (ITC); Steven de Jong, Theo van Asch and Rens van Beek (Utrecht University); Santiago Begueria (University of Zaragoza, Spain); Thomas Glade (University of Vienna); Jean-Philippe Malet (CNRS, Strasbourg); Dr. Sankar (CESS); P.K. Champati Ray and R.C. Lakhera (IIRS); K. Vinod Kumar (NRSC). The project was possible due to the efforts made by Dr. N. Rajendran of GSI. The research was also a contribution to the EU FP7 SafeLand project (www.safeland-fp7.eu) in which India is one of the two countries selected outside of Europe.

#### References

- Anbalagan, R., 1992. Landslide hazard evaluation and zonation mapping in mountainous terrain, Engineering Geology 32 (4), 269-277.
- Begueria, S., van Asch, T.W.J., Malet, J.P., and Grondahl, S., 2009. A GIS-based numerical model for simulating the kinematics of mud and debris flows over complex terrain: Natural Hazards and Earth System Sciences 9 (6), 1897-1909.
- Bhandari R.K., 2006. The Indian Landslide Scenario, Strategic Issues and Action Points, A Key Note address – Technical Session on Landslides) First India Disaster Management Congress, New Delhi, 29-30 November 2006.
- BIS, 1998. Preparation of landslide hazard zonation maps in mountainous terrains, IS 14496 (Part - 2) - Guidelines: New Delhi, Bureau of Indian Standards, Government of India.
- BIS, 2002. Criteria for earthquake resistant design of structures: General provisions and buildings, Bureau of Indian Standards (BIS) IS 1893:2002 (Part-1).
- BMTPC 2003. Landslide Hazard Zonation Atlas of India, Published by Building Materials and technology Promotion Council, Government of India and Anna University, Chennai.
- Bonham-Carter, G.F., 1994. Geographic Information Systems for Geoscientists: Modeling with GIS. Pergamon, Elsevier Science Ltd., 398 pp.
- Das, I.C., Sahoo, S., Van Westen, C.J., Stein, A. and Hack, R., 2010. Landslide susceptibility assessment using logistic regression and its comparison with a rock mass classification system, along a road section in the northern Himalayas (India). Geomorphology 114 (4), 627-637.
- Das, I., Stein, A. (Promotor) and Kerle, N. (assistant promotor) 2011. Spatial statistical modelling for assessing landslide hazard and vulnerability. PhD thesis University of Twente; summaries in Dutch and English. ITC Dissertation 192, ISBN: 978-90-6164-312-8
- Ghosh, S., van Westen, C.J., Carranza, E.J.M., Ghoshal, T., Sarkar, N., Surendranath, M., 2009a. A quantitative approach for improving the BIS (Indian) method of medium-scale landslide susceptibility. Journal of the Geological Society of India 74, 625-638.
- Ghosh, S., van Westen, C.J., Carranza, E.J.M., Jetten, V.G., 2009b.
  Generation of event based landslide inventory maps in a data scarce environment: case study around Kurseong, Darjeeling district, West Bengal, India. In: Malet, J.P., Remaitre, A., Bogaard, T. (Eds.). Landslide processes : from geomorphologic mapping to dynamic modeling : proceedings of the landslide processes. European Centre on Geomorphological Hazards (CERG), Strasbourg, France, 37-44.
- Ghosh, S., Carranza, E.J.M., 2010. Spatial analysis of mutual fault/fracture and slope controls on rocksliding in Darjeeling Himalaya, India. Geomorphology 122, 1-24.
- Ghosh, S., Günther, A., Carranza, E.J.M., van Westen, C.J., Jetten, V.G., 2010. Rock slope instability assessment using spatially distributed structural orientation data in Darjeeling Himalaya (India). Earth surface processes and landforms 35, 1773-1792.
- Ghosh, S., Carranza, E.J.M., van Westen, C.J., Jetten, V.G., Bhattacharya, D.N., 2011a. Selecting and weighting of spatial predictors for empirical modeling of landslide susceptibility in Darjeeling Himalaya (India). Geomorphology 131 (1-2), 35-56.
- Ghosh, S., van Westen, C.J., Carranza, E.J.M., Jetten, V.G., 2011b. Integrating spatial, temporal and magnitude probability for medium scale landslide hazard and risk analysis in Darjeeling Himalayas (India). Landslides (submitted).
- Ghosh, S., van Westen, C.J., Carranza, E.J.M., Jetten, V.G., Cardinali, M., Rossi, M., Guzzetti, F., 2011c Generating event-based landslide maps in a data-scarce Himalayan environment for

estimating temporal and magnitude probability. Engineering Geology (in press).

- Ghosh, S., Jetten, V.G. (Promotor), van Westen, C.J. (assistant promotor) and Carranza, E.J.M. (assistant promotor), 2011d. Knowledge guided empirical prediction of landslide hazard : ebook. Enschede, University of Twente Faculty of Geo-Information and Earth Observation ITC, ITC Dissertation 190, ISBN: 978-90-6164-310-4.
- Günther, A., 2003. SLOPEMAP: programs for automated mapping of geometrical and kinematical properties of hard rock hill slopes. Computers and Geoscience, 865-875.
- Jaiswal P., van Westen C.J., 2009. Estimating temporal probability for landslide initiation along transportation routes based on rainfall thresholds. Geomorphology 112, 96-105.
- Jaiswal P., van Westen C.J., Jetten V., 2010a. Quantitative landslide hazard assessment along a transportation corridor in southern India. Engineering Geology 116, 236-250.
- Jaiswal P., van Westen C.J., Jetten V., 2010b. Quantitative assessment of direct and indirect landslide risk along transportation lines in southern India. Nat. Hazards Earth Syst. Sci. 10, 1253-1267
- Jaiswal P., van Westen C.J., Jetten V., 2011a. Quantitative estimation of landslide risk from rapid debris slides on natural slopes in the Nilgiri hills, India. Nat. Hazards Earth Syst. Sci., DOI 10.5194/nhess-11-1723-2011..
- Jaiswal P., van Westen C.J., Jetten V., 2011b. Quantitative assessment of landslide hazard along transportation lines using historical records. Landslides, DOI 10.1007/s10346-011-0252-1.
- Jaiswal, P., Jetten, V.G. (Promotor), van Westen, C.J. (assistant promotor) and Ayyasami, K. (assistant promotor), 2011c. Landslide risk quantification along transportation corridors based on historical information : e-book. Enschede, University of Twente Faculty of Geo-Information and Earth Observation ITC, ITC Dissertation 191, ISBN: 978-90-6164-311-1.
- Jaiswal P., van Westen C.J., 2011d. Frequency-size relation of shallow debris slides on cut slopes along a railroad corridor A case study from Nilgiri hills, Southern India. Natural Hazards, under review.
- Kuriakose, S.L, Jetten, V.G., van Westen, C.J., Sankar, G. and van Beek, L.P.H., 2008. Pore water pressure as a trigger of shallow landslides in the western Ghats of Kerala, India: some preliminary observations from an experimental catchment. In: Physical geography 29 (4), 374-386.
- Kuriakose, S.L., van Beek, L.P.H. and van Westen, C.J., 2009a Parameterizing a physically based shallow landslide model in a data poor region. In: Earth surface processes and landforms, 34 (6), 867-881.
- Kuriakose S.L., Sanjaya Devkota, D.G Rossiter, V.G Jetten, 2009b. Prediction of soil depth using environmental variables in an anthropogenic landscape, a case study in the Western Ghats of Kerala, India. Catena, 79(1), 27-38.
- Kuriakose, S.L., Jetten, V.G. (Promotor), de Jong, S.M. (Promotor), van Westen, C.J. (co-promotor) and van Beek, L.P.H. (copromotor), 2010. Physically - based dynamic modelling of the effect of land use changes on shallow landslide initiation in the Western Ghats of Kerala, India + CD-ROM with appendices. Enschede, University of Twente Faculty of Geo-Information and Earth Observation ITC, ITC Dissertation 178, ISBN: 978-90-6164-298-5.
- Kuriakose, S.L. L.P.H van Beek, 2011. Plant root strength and slope stability. In Glinski J, Horabik J, Lipiec J (eds). Encyclopaedia of Agrophysics (Encyclopaedia of Earth Sciences Series), Springer. DOI 10.1007/978-90-481-3585-1
- Martha, T.R., Kerle, N., van Westen, C.J., Jetten, V. and Vinod Kumar, K. , 2010a. Effect of sun elevation angle on DSMs derived

from Cartosat - 1 data. Photogrammetric Engineering and Remote Sensing 76 (4), 429-438.

- Martha, T.R., Kerle, N., van Westen, C.J., Jetten, V. and Vinod Kumar, K. , 2010b. Landslide volumetric analysis using Cartosat -1 derived DEMs. IEEE Geoscience and Remote Sensing Letters 7 (3), 582-586.
- Martha, T.R., Kerle, N., van Westen, C.J., Jetten, V. and Vinod Kumar, K., 2010c. Characterising spectral, spatial and morphometric properties of landslides for semi - automatic detection using object - oriented methods. Geomorphology 116 (1-2), 24-36.
- Martha, T.R., Kerle, N., van Westen, C.J., Jetten, V. and Vinod Kumar, K., 2011a. Segment optimisation and data-driven thresholding for knowledge-based landslide detection by objectbased image analysis. IEEE Transactions on Geoscience and Remote Sensing (In press).
- Martha, T.R., Kerle, N., van Westen, C.J., Jetten, V. and Vinod Kumar, K., 2011b. Object-oriented analysis of multi-temporal panchromatic images for creation of historical landslide inventories. ISPRS Journal of Photogrammetry and Remote Sensing (In revision).
- Martha, T.R., Kerle, N., van Westen, C.J., Jetten, V. and Vinod Kumar, K., 2011c. Landslide hazard and risk assessment using landslide inventories created semi-automatically by objectoriented analysis. Journal of the Geological Society of India (In revision).
- Martha, T.R., Jetten, V.G. (Promotor), van Westen, C.J. (assistant promotor) and Kerle, N. (assistant promotor), 2011d. Detection of landslides by object oriented image analysis : e-book. Enschede, University of Twente Faculty of Geo-Information and Earth Observation ITC, ITC Dissertation 189, ISBN: 978-90-6164-309-8.
- Nadim, F., Kjekstad, O., 2009. Assessment of Global High-Risk Landslide Disaster Hotspots. In: Sassa, K., Canuti, P. (Eds.), Landslides - Diaster Risk Reduction. Springer, 213-221.
- NDMA, 2009. Management of Landslides and Snow Avalanches, 2009. National Disaster Management Authority (NDMA), Government of India, New Delhi, 144 pp.
- OFDA/CRED, 2010. EM-DAT International Disaster Database www.em-dat.net. Université Catholique de Louvain, Brussels, Belgium.
- Petley, D.N., Dunning, S.A., Rosser, N.J., 2005. The analysis of global landslide risk through the creation of a database of worldwide landslide fatalities. In: Hungr, O., Fell, R., Couture, R., Eberhardt, E. (Eds.), Landslide risk management. Taylor & Francis Group, London, 367-373.
- Rajarathnam, S. and Ganapathy, G.P., 2006. Landslide hazard zonation of India using GIS techniques. Thematic Session – Landslide, Avalanche and Other Mass Movements. First Indian Disaster Management Congress, 29-30 November 2006, New Delhi, India.
- Sarkar, S. and Kanungo, D.P., 2005, Landslide Hazard Zonation in India: A Review, Int. Conf. on Geotechnical Engineering for Disaster Management & Rehabilitation. Kyoto University, Japan.
- Sharda, Y.P 2008. Landslide studies in India, Glimpses of Geoscience Research In India, The Indian report to IUGS 20042008. Indian National Science Academy, Silver Jubilee Volume, 98-101.
- Van Westen, C.J., Castellanos, E., Kuriakose, S.L. (2008) Spatial data for landslide susceptibility, hazard, and vulnerability assessment: An overview. Engineering Geology 102, 112-131.